

Acrylic Primer
Streichgrund

Granol Plus Acrylic Primer

Material:

Quartz, containing first coat on synthetic resin dispersion basis.

Characteristics:

Torrential rainproof bonding agent on all supporting, dry and clean substrates. Water vapour permeable, not liquid, low stress, environmental friendly.

Application:

Ideal first coat for all synthetic resin bonded final coats, as well as for synthetic resin treated, mineral thin coat render indoors and outdoors.

Technical data:

Density: 1,60 kg/dm³

Substrates:

Substrates must be flat, supporting, clean and dry. Loose render parts can be removed or smoothed if necessary.

The directions of DIN 18363, the VOB, part C as well as the BFS-instruction sheets of the affected areas to be processed in the latest revision are to be regarded.

With dubious substrates please ask for our consulting services.

Processing:

Process with paint brush, brush or lamb skin roller, depending on substrate. Granol Streichgrund can be diluted with up to 10% water, depending on the substrate. Stir properly before use. The fresh Streichgrund must be protected against torrential rain and too fast drying. Especially with direct sunlight and wind influence suitable countermeasures must be taken, such as e.g. covering of the façade or of the scaffold.

Do not process with substrate and / or environmental temperatures below + 5° C.

Tools and equipment must be cleaned with water immediately after use. Surrounding building parts, such as windows, window-sills etc. must be properly covered.

Consumption:

0,2 - 0,3 kg/m² per paint coating with structureless substrates.

For an exact calculation the exact consumption must be determined by applying a test coating onto the object.

Delivery:

Ready for processing in 6 / 12 / 18 / and 25-kg containers.

Stocking:

Store in a cool and frost-free area. Protect against direct sunlight Can be stored in a closed container for at least 1 year. Broached containers must be processed within a short period of time.

Acrylic Primer Streichgrund

Colour tones:

White, as a standard article. When ordering, matched to the colour tone of the top render.
Can be toned with Granol Vollton- and Abtönfarbe.

There is an extensive choice of colour tones available. See our original samples. Special colour tones can be made on request. It is not possible to use colour tones with brightness references below 20.

Colour tone differences on the processed surface to the corresponding trials and treatments cannot be avoided because of the natural raw material choices and weather influenced drying processes. In the event of subsequent deliveries the remaining part of the material must be mixed with the new material on a continuity basis, to guarantee the same colour.

Special considerations:

Surfaces that should not be treated must be covered when spraying. Do not mix binders and additives.

Processing should be carried out according to the safety directions. All safety-related data can be found in the safety data sheets.

Directions for dangerous situations / safety advice:

Do not breathe the dust.

Irritating to eyes and skin.

Risk of serious damage to the eyes.

Avoid contact with the eyes and skin.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

May cause sensitisation by skin contact.

For all other data relating to safety please refer to the safety data sheet.

Disposing:

Only emptied containers can be returned for recycling. Waste material must be dried before disposal according to key nr. 91206 (building waste).

Our application recommendations, whether verbal, written or as graphics, are given to the best of our knowledge and the state of the art. Information about values, quantities etc. are based on approximate figures. The recommendations do not constitute a legally binding warranty of quality. In particular no liability claims may be based on these recommendations; the provisions of the product liability law remain unaffected.

The recommendations do not release the purchaser from his own duty to test the product or from his own responsibility, and in particular they do not release the purchaser from compliance with the relevant technical guidelines, regulations, DIN and laws.

Publication of a revised version of this technical information sheet due to technical progress invalidates all older versions of this document.